



dimensions (w x d x h)	number of shelves	possibility of partition	installed power input	climatic category	LA noisiness	exhibition area	loading capacity of exhibition area	loading capacity of shelf	weight	coolant	type of glass
1500 x 1180 x 1360	1	no	1050 W	3	< 60 dB	1,3 m <sup>2</sup>	30 kg	5 kg	280 kg	R 404A	round, hardened side hardened double-glazed with insulating

A self-service refrigerating display case for the sale of goods at temperatures from +4° to +8°C. The front glass with the thickness of 6 mm is tilting, set in AL elox profiles and equipped in profile. GN vessels are installed in the upper section of the display area. The lower refrigerated space for storing GN vessels is closed by insulated door. The bottom display board of stainless steel design and display case body is formed by decorated laminated wood-chip boards. The side glasses are hardened, double, insulating. A sliding door double-glazed with insulating glass from the shop attendant side fitted with end stop buffers. Dynamic cooling. A cooling unit with the function of condenser self-cleaning and automatic evaporating of waste condensate by residual heat from the cooling circuit. Lighting by means of AL line lamps fitted with up-to-date LED chips. A digital electronic regulator for optimum control of the display case operating cycles.

The guarantee period of the product is 12 months. Guarantee and post-guarantee repairs are carried out by the producer or, after an agreement, by the service centre in the place of the user. Producer reserves the privilege for changeover.