



dimensions (w x d x h)	number of shelves	possibility of partition	installed power input	climatic category	LA noisiness	exhibition area	loading capacity of exhibition area	loading capacity of shelf	weight	coolant	type of glass
1050 x 755 x 1360	3	yes	750 W	3	< 60 dB	1,7 m ²	30 kg	5 kg	200 kg	R 404A	round 6mm thick uncured
1350 x 755 x 1360		yes	900 W			2,2 m ²			250 kg		

A self-service refrigerating display case for presentation of chocolate products. Designed for the sale of goods at temperatures from + 16 ° to + 20 ° C, the humidity inside the display case is 40 - 60%. The indoor climate of showcases slows aging (choking) of chocolate. The front non-hardened rounded glass with the thickness of 6 mm is tilting and equipped with chain arresters. The bottom display board of stainless steel design and display case body is formed by decorated laminated wood-chip boards. The shelves are made of hardened glass. A sliding door double-glazed with insulating glass from the shop attendant side fitted with end stop buffers. Dynamic and static cooling - minimum air flow inside the display case . A cooling unit with the function of condenser self-cleaning and automatic evaporating of waste condensate by residual heat from the cooling circuit. Lighting by means of AL line lamps fitted with up-to-date LED chips. A digital electronic regulator for optimum control of the display case operating cycle.

The guarantee period of the product is 24 months. Guarantee and post-guarantee repairs are carried out by the producer or, after an agreement, by the service centre in the place of the user. Producer reserves the privilege for changeover.